


HIDDEN IP IR CAMERA DUMMY PIR HOUSING

IV-390IP537



- 1/2.7" CMOS Sensor
- 2 Mega-Pixel
- True Day & Night (IR Cut Removable)
- H.265 (HEVC) Compression
- 0 Lux (IR On) Min. Illumination
- ONVIF
- True WDR / BLC / HLC
- 3D Noise Reduction
- Motion Detection and Privacy Masking
- Analytics Support
- 3.6mm Mega-Pixel Lens
- 30m IR Illumination
- PoE Support
- 1 Way Audio (Built-In Microphone)
- CVBS
- Local Storage

Specifications (Based on v4.2.1)

Camera	Video	Model	I3-390IP536
		Image Sensor	1/2.7" CMOS (16:9)
		Effective Pixels	1920x1080
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	1-25/30FPS
		Day & Night	ICR
		Min. Illumination	Day: 0.022lux / Night: 0.01lux (@F1.8, AGC On) 0lux with IR on
		Audio	Audio compression
	Communication		One-way Audio
	Image Processing	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		Image Enhancement	True WDR (120dB) / BLC / HLC / ROI
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
		Motion Detection	Yes
Compression	Analytics	Camera Tampering, Line Crossing, Sterile Area, Smart Search	
	Video Compression	H.265 / H.264 / MJPEG (Sub-Stream Only)	
	Resolution	1080P (1920x1080), 720P (1280x720), D1, CIF	
	Multi-Stream	Main Stream: 1920x1080 / 1280x720 (1~25/30FPS) Sub-Streams D1 / CIF (1~25/30FPS)	
	Bit rate	64Kbps ~ 4Mbps@H.265 / 128Kbps ~ 6Mbps@H.264	
	Encode Mode	VBR/CBR	
Image Quality	Five levels under VBR; Free adjustment under CBR		

Housing	IR Distance	10m (20 IR LED)
	Lens (Field of View)	3.7mm (78.9°)
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	None
	Bracket	3-Axis Wall Bracket
Connectivity	Dimensions	95*69.5*58mm
	Weight(gross)	269g
	Network	RJ45 (+PoE)
	Power	DC Socket / PoE
	Analog Video Output	No
	Audio Connectivity	Built-In Microphone or 1Ch Audio input
	SD Card	Support Event recording over TF (128GB Max)
	RS485	No
	Alarm	No
	Network	Remote Monitoring
User Access		Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
Network Protocol		TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP
ONVIF		Yes
Others	Ethernet	100Mbps
	PoE	Yes
	Power Supply	DC12V/~420mA / PoE/~4.8W
Work Environment	-20 C ~ 50 C, 10%~90% Humidity	

