K636
Wired LED Keypad

▶ Features

▸ Controls and displays up to 10 zones; partition 1 only
▸ StayD™ Status LED
▸ Arm, Sleep, Stay and Off keys illuminate to indicate partition status
▸ Patented Key Light display (button lights up to indicate an open zone)
▸ Adjustable key backlight
▸ Available in multiple languages

▶ Specifications

Input Voltage	12 to 14 Vdc
Current Consumption	Minimum: 15mA
	Maximum: 30mA
PGM Output	1 (follows arm status)
Operating Temperature	0 to 50 °C (32 to 122 °F)
Dimensions	14.3 x 7.8 x 2.3 cm (5.6 x 3.1 x 0.9 in.)

ZX8SP
8-Zone Expansion Module

▶ Features

▸ 8 zone inputs
▸ 1 PGM output (50 mA PGM)
▸ Uses zone input as an anti-tamper switch input

▶ Specifications

Input Voltage	12 to 16 Vdc
Current Consumption	28 mA
Operating Temperature	-20 to 50 ℃ (-4 to 122 ℉)
Dimensions	14 x 4.5 x 1.8 cm (5.5 x 1.8 x 0.7 in.)

For full details on:

	ZX8 8-Zone Expansion Module Refer to page 13		**HUB2** 2-Port Hub and Bus Isolator Refer to page 18

CE